

4

3

DWG NO

127-7503D

SH

2

REV

D

2

1

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF  
DYTRAN INSTRUMENTS INC. ANY REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF DYTRAN INSTRUMENTS INC. IS PROHIBITED

D

D

C


C

B

B

A

A



RECOMMENDED MOUNTING PREPARATION: MODEL 6366  
PREPARE MOUNTING SURFACE,  $\phi 1.25$  [31.2] MIN, FLAT TO .001 TIR.  
TAP 1/4-28 UNF-2B  $\nabla$  .200 [5.1] MIN. TORQUE TO 12-15 Lb-in.

RECOMMENDED MOUNTING PREPARATION: MODEL 6691  
PREPARE MOUNTING SURFACE,  $\phi 1.25$  [31.2] MIN, FLAT TO .001 TIR.  
TAP M6 X 1  $\nabla$  .200 [5.1] MIN. TORQUE TO 12-15 Lb-in.

		<b>MASTER</b> ONLY IF IN RED	
TITLE: OUTLINE/INSTALLATION DWG, TRIAxIAL DC ACCELEROMETER, 7503D SERIES			
SIZE <b>B</b>	CAGE CODE <b>2W033</b>	DWG NO <b>127-7503D</b>	REV <b>D</b>
SCALE: 2:1		SHEET 2 OF 2	

4


3

2

1

Model Number 7503D5		PERFORMANCE SPECIFICATION				DOC NO PS7503D5
		TRIAXIAL VARIABLE CAPACITANCE ACCELEROMETER				REV K, ECN 15137, 06/13/19



- VARIABLE CAPACITANCE TECHNOLOGY
- $\pm 4V$  DIFFERENTIAL OUTPUT
- HERMETICALLY SEALED
- DC RESPONSE

ENGLISH		SI	
PHYSICAL			
Weight, Max	1.3 oz	38 grams	
Connector	9-pin, 5/16-32 UNEF-2A	9-pin, 5/16-32 UNEF-2A	
Material	Titanium Alloy	Titanium Alloy	
Sensing Technology	MEMS	MEMS	
PERFORMANCE			
Input Range	$\pm 50$ g	$\pm 490.5$ m/s <sup>2</sup>	
Frequency Response ( $\pm 5\%$ )	0 - 1700 Hz	0 - 1700 Hz	
Frequency Response ( $\pm 3dB$ )	0 - 2700 Hz	0 - 2700 Hz	
Resonant Frequency	>3000 Hz	>3000 Hz	
Sensitivity Differential, $\pm 5\%$ [1]	80 mV/g	8.2 mV/m/s <sup>2</sup>	
Output Noise, Differential, Typ	69 $\mu g$ rms/v Hz	677 $\mu m/s^2$ /v Hz	
Non-Linearity, Max [2]	0.5 % F.S	0.5 % F.S	
Cross Axis Sensitivity, Max	3 %	3 %	
Scale Factor Calibration Error, Max.	1 %	1 %	
Zero Measured Output	$\pm 50$ mV	$\pm 50$ mV	
ENVIRONMENTAL			
Maximum Mechanical Shock (0.1 ms)	$\pm 2000$ gpk	$\pm 19620$ m/s <sup>2</sup> peak	
Bias Temperature Shift, Max [3]	111 (ppm of span)/°F	200 (ppm of span)/°C	
Bias Calibration Error, Max	0.5 % of span	0.5 % of span	
Operating Temperature Range [4]	-67 to +257 °F	-55 to +125 °C	
Scale Factor Temperature Shift [3]	-111 to +111 ppm/°F	-200 to +200 ppm/°C	
Seal	Hermetic	Hermetic	
ELECTRICAL			
Output Common Mode Voltage, Typ	2.5 VDC	2.5 VDC	
Output Impedance	<10K $\Omega$	<10K $\Omega$	
Operating Voltage	+6 to +33 VDC	+6 to +33 VDC	
Operating Current (AOP & AON open), Max	35 mA Dc	35 mA Dc	
Power Supply Rejection Ratio	>65 dB	>65 dB	
Ground Isolation	>30 MQ	>30 MQ	

**This family also includes:**

Model	Input Range (g)	Frequency Response, $\pm 3dB$ (Hz)	Sensitivity Differential, $\pm 5\%$ (mV/g)	Max.Shock (0.1ms) g (peak)	Noise Differential ( $\mu g$ /vHz)
7503D1	$\pm 2$	0-400	2,000	2000	10.5
7503D2	$\pm 5$	0-800	800	2000	12
7503D3	$\pm 10$	0-1000	400	2000	18
7503D4	$\pm 25$	0-1500	160	2000	44
7503D6	$\pm 100$	0-2500	40	2000	122
7503D7	$\pm 200$	0-5000	20	2000	290
7503D8	$\pm 400$	0-4000	10	2000	400
7503D9	$\pm 5(X\&Y), \pm 25(Z)$	0-800(X&Y), 0-1500(Z)	800(X&Y), 160(Z)	2000	12(X&Y), 44(Z)
7503D10	$\pm 5(X\&Y), \pm 50(Z)$	0-800(X&Y), 0-2700(Z)	800(X&Y), 80(Z)	2000	12(X&Y), 69(Z)

Refer to the performance specifications of the products in this family for detailed description


**Supplied Accessories:**

- 1) Accredited calibration certificate (ISO 17025)
- 2) Mounting stud, Model 6360, 1/4-28 UNF-2A, Qty 1
- 3) Mounting stud, Model 6691, 1/4-28 UNF-2A to M6 X 1, Qty 1
- 4) Mounting screws, Model 6753A1, 8-32 x 1.0, Qty. 2
- 5) Mounting screws, Model 6687A1, M4x0.7 x 25mm, Qty. 2
- 6) Flat washers, Model 6754, Qty. 2

**Notes:**

- [1] Single ended sensitivity is half of values shown. (Ref. at 100 Hz)
- [2] -90% to +90% of Full Scale.
- [3] Over the rated temperature range.
- [4] Limit operating voltage to +24VDC when temperature is greater than 240°F (115°C).
- [5] In the interest of constant product improvement, we reserve the right to change specifications without notice.

It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary overtime. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts.



Units on the line drawing are in inches. Refer to 127-7503D for more information.



21592 Marilla Street, Chatsworth, California 91311 Phone: 818.700.7818 Fax: 818.700.7880 [www.dytran.com](http://www.dytran.com)  
For permission to reprint this content, please contact [info@dytran.com](mailto:info@dytran.com)